

# Signature

مشخصات فنی توری فایبر گلاس پشت سنگ سیگنچر

| SIGNATURE PRESIGE 190 |                                    |                                    |
|-----------------------|------------------------------------|------------------------------------|
| 1                     | CODE                               | 60-1×2                             |
| 2                     | WEAVE                              | PLAIN                              |
| 3                     | YARN<br>(tex)                      | WARP<br>WEFT<br>30×2<br>67         |
| 4                     | DENISTY<br>COUNT/25mm              | WARP<br>WEFT<br>10<br>20           |
| 5                     | MESH SIZE(MM)                      | WARP<br>WEFT<br>1<br>2             |
| 6                     | FINISHED WEIGHT(g/m <sup>2</sup> ) | 60(± 5)                            |
| 7                     | TENSILE<br>STRENGTH<br>N/5cmx20cm  | WARP<br>WEFT<br>≥ 600<br>≥ 700     |
| 8                     | WOVEN STRUCTURE                    | LENO                               |
| 9                     | COUNTENT OF RESIN %(>=)            | 15                                 |
| 10                    | ROLL SIZE                          | 1.9 m × 200 mL                     |
| 11                    | STANDARD COLOR                     | WHITE                              |
| 12                    | APPLICATION                        | Reinforcement marble               |
| 13                    | PACKING                            | 1 ROLL/CARTON                      |
| 14                    | THREAD MARKING                     | BLUE & YELLOW LINES AT<br>ONE EDGE |

## Storage:

Keep mesh from prolonged exposure to weather.

Do not allow petroleum products come into contact with mesh.

## Shelf life:

Two(2) years or more when properly stored in unopened packages.